



## INLINE® USB POWER SUPPLY, GAN CHARGER, 2X USB-C, 1X USB-A, PD 3.0, WITH SAFETY SOCKET AND 1.5M CABLE, WHITE

Experience the powerful and compact 65W GaN charger with 2x USB-C port, 1x USB-A port, 1x safety socket and 1.5m connection cable - the perfect solution for fast and efficient charging of multiple devices at the same time! Thanks to GaN (Gallium Nitride) technology, this power supply is highly efficient and allows for better performance while maintaining a smaller size. Electrons are conducted up to 1.000x more efficiently than traditional silicon semiconductors, resulting in less heat build-up and energy loss. The 65W GaN charger also supports Power Delivery 3.0 on the USB-C ports and Quickcharge 4+ on the USB-A port, and offers multiple output options.

- 2x PD USB-C / 1x QC USB-A charger, earthing contact socket
- USB-C PD output 1: 5VDC/3A(15W) - 9VDC/3A(27W) - 12VDC/3A(36W) - 15VDC/3A(45W) - 20VDC/3,25A (max. 65W), PPS: 3,3-11VDC/5A (max. 55W)
- USB-C PD output 2: 5VDC/3A(15W) - 9VDC/3A(27W) - 12VDC/2.5A(30W) - 15VDC/2A(30W) - 20VDC/1.5A (max. 30W)
- USB-A QC output: 5VDC/4.5A(22.5W) - 4.5VDC/3A(22.5W) - 9VDC/3A(27W) - 12VDC/2.5A(30W) - 20VDC/1.5A (max. 30W)
- Ground socket: 230V AC 50/60Hz, 16 A max., 3680 W max.
- Power Delivery 2.0, 3.0 and Quick Charge 2.0, 3.0, 4.0, 4.0+ compatible
- Input voltage: 220-250V AC
- Input AC frequency: ~50/60 Hz, 16 A max.
- USB output voltage: 3.3-20.0V DC
- USB output current: 5.0 A max.
- USB output power: 65.0 W
- Power consumption at no load: 0.18 W
- Overvoltage and short circuit protection
- Thermal protection: if the temperature of the power supply is too high, it switches off automatically and resumes charging automatically after cooling down
- Dimensions (LxWxH): approx. 107x48x40mm
- Weight: approx. 400g
- Length of connection cable: 1.5m



**EAN: 4043718316526**  
**ART.-NR.: 315181**