

NETZWERKKABEL

Cat.6, S/FTP (PMF), 250MHz, PVC-Mantel, Kupfer





	grau	schwarz	transparent	weiß	blau	rot	gelb	grün	orange	braun	pink	violett
0,25m	76422	76422S	76422T	76422W	76422B	76422R	76422Y	76422G	76422O	76422K	76422M	76422P
0,3m	76433	76433S	76433T	76433W	76433B	76433R	76433Y	76433G	76433O	76433K	76433M	76433P
0,5m	76450	76450S	76450T	76450W	76450B	76450R	76450Y	76450G	76450O	76450K	76450M	76450P
1,0m	76411	76411S	76411T	76411W	76411B	76411R	76411Y	76411G	76411O	76411K	76411M	76411P
1,5m	76412	76412S	76412T	76412W	76412B	76412R	76412Y	76412G	76412O	76412K	76412M	76412P
2,0m	76402	76402S	76402T	76402W	76402B	76402R	76402Y	76402G	76402O	76402K	76402M	76402P
3,0m	76403	76403S	76403T	76403W	76403B	76403R	76403Y	76403G	76403O	76403K	76403M	76403P
5,0m	76405	76405S	76405T	76405W	76405B	76405R	76405Y	76405G	76405O	76405K	76405M	76405P
7,5m	76407	76407S	76407T	76407W	76407B	76407R	76407Y	76407G	76407O	76407K	76407M	76407P
10m	76400	76400S	76400T	76400W	76400B	76400R	76400Y	76400G	76400O	76400K	76400M	76400P
15m	76415	76415S	76415T	76415W	76415B	76415R	76415Y	76415G	76415O	76415K	76415M	76415P
20m	76420	76420S	76420T	76420W	76420B	76420R	76420Y	76420G	76420O	76420K	76420M	76420P
25m	76425	76425S	76425T	76425W	76425B	76425R	76425Y	76425G	76425O	76425K		
30m	76430	76430S	76430T	76430W	76430B	76430R	76430Y	76430G	76430O	76430K		
40m	76440	76440S	76440T	76440W	76440B	76440R	76440Y	76440G				
50m	76455	76455S	76455T	76455W	76455B	76455R	76455Y	76455G				
100m*	76499	76499S	76499T	76499W	76499B	76499R	76499Y	76499G	76499O			

*ohne Stecker, nicht konfektioniert



- Äußere Isolierung
- Geflechtsschirmung
- Folienbeschichtung der Leiterpaare
- Leitersolothion
- Leiterader



- Wiederverschiebbare, POS-taugliche PE-Beutel mit EAN-Code
- Gesamt-Geflechtschirmung und PMT - Pärweise in Metallfolie (alte Bezeichnung: S-STP PMF)
- Angespitzter Knickschutz und Rastrabenschutz
- Stecker mit Längenangabe auf der Unterseite
- 1:1 Belegung nach EIA/TIA 568B

www.inline-info.com

INLINE® MOUSE PAD, LASER, ULTRA-THIN, 220X180X0.4MM

Ultra-thin mouse pad, especially suitable for optical mice and laser mice

- Ultra-thin, only 0.4 mm high
- Optimized surface for precise working
- Anti-slip bottom
- Supports mice with laser sensor and optical scanning
- Dimensions: 220x180x0, 4mm
- In an attractive retail packaging with euro hole



Art. Nr.	Farbe	EAN
55456I	Mehrfarbig	4043718232680
55456B	Blau	4043718193851
55456R	Rot	4043718193868